

NEW



## Electric Vehicle Charging **Lite**



**Pilot EV Lite Chargepoint.**  
Surface mounted, bluetooth/Wi-Fi EV charging solution.

### **Key features**

- Available in socket version or cable version (Tethered or Un-Tethered)
- Local\remote operation via mobile APP
- Built in A-EV RCD
- Available in residential or SME version
- Remotely adjustable power output
- Bespoke design options
- User access management
- 5 year warranty

## Supported App Feature Schemes

---

Remote start/stop  
Users management  
Charging status (A & kWh)  
Scheduled charging  
Charging history

## Safety and Certification

---

CE & TUV compliant acc. IEC61851  
Built-In A-EV RCD per socket  
Over power protection  
Dynamic load management

## Environmental Conditions

---

Approved for both indoor & outdoor installations  
**Operating temperature:** (-25°C) to (+55°C)  
**Non-operating temperature:** (-30°C) to (+70°C)  
**Humidity:** Up to 100% non-condensing  
**Ingress protection rating:** IP54  
**Impact protection rating:** IK8

## Electrical Data

---

**Input Voltage:** 230 Vac, Single phase + N + PE  
**Input Current:** 32Amax  
**Output Power:** 7.4kW, 32Amax  
**Socket:** IEC 62196 Type 2 connector

## Dimensions & Weight

---

**WxHxD:** 310x480x170 mm, 5kg

## Communication

---

Wi-Fi/ Bluetooth  
OCPP 1.6 ready, OTA updates