

NEW



Electric Vehicle Charging **Classic Double**



Pilot EV Double Classic Chargepoint.
Surface mounted, EV charging solution.

Key features

Dual Mode 3 charging station

Charging two cars simultaneously with no output power degradation

Intuitive usage using 8" touch screen - Optional

Powered by Nayax VPOS Touch allowing complete telemetry and cashless solution

Accepts all cashless payments methods

- Debit and Credit Cards
- Mobile, NFC Payments
- Prepaid cards and Closed environment solutions
- Swipe, Contact and Contactless

Supported Payment Schemes

Contact Crad: EMV Level + Level 2
Contactless: EMV Level 1
Visa PayWave, Mastercard PayPass
Magnetic Stripe Card: Tracks 1,2,3 - JIS II
Other Cards Supported: NFC, MIFARE, HID-iClass, FeliCa

Safety and Certification

CE & TUV compliant acc. IEC61851
Built-In A-EV RCD per socket
Over power protection

Environmental Conditions

Approved for both indoor & outdoor installations
Operating temperature: (-20°C) to (+55°C)
Non-operating temperature: (-30°C) to (+70°C)
Humidity: Up to 95% non-condensing
Ingress protection rating: IP54

Electrical Data

Input Voltage: 360-440 Vac, Three phase + N + PE
Input Current: 64Amax
Output Power: 22kW, 32Amax per socket
Socket: IEC 62196 Type 2 connector

Dimensions & Weight

WxHxD: 410x680x160 mm, 14kg

Communication

GSM / GPRS / CDMA / Ethernet
OCPP 1.6 ready, OTA updates